

# **Material Safety Data Sheets**

**Section 1: Product and Company Identification** 

**Product:** Arline WPC system

Manufacturer: ARLINE Composite – Arslan Dis Tic San Ltd. Sti

Add: Sanayi Cad.No:27 35100 Bornova – Izmir / Turkey

Tel: 00 90-232-3889494 Fax: 00 90 232 3880151

Effect Date: April, 2009 Update Date: May, 2013

Section 2: Composition, Information on Ingredients

Component Name: Composition Amount Wood Fiber (Sawdust): 50-60% Polyethylene: 35-45%,

various Chemical Additive:5%

Section 3: Hazards Identification

In normal use, the product is not hazardous. However, this product may be cut or finished in ways which produce wood dust fibers. Certain wood fibers are considered hazardous if the airborne concentration exceeds the OSHA or ACGIH exposure limits for long periods of time. Exposure to such fibers is considered unlikely with this product; all sawdust in the board

is fully stabilized in the plastic resin matrix.

**Section 4: Emergency and First Aid Procedures** 

**Inhalation:** This material is not expected to present an inhalation hazard.

**Eyes:** Flush sawdust or fines from eyes with water; if irritation occurs, obtain

Medical attention.

**Skin:** This material is not expected to present a skin contact hazard.

**Ingestion:** No adverse affects expected from ingestion.

**Section 5: Fire and Explosion Data** 

Flash Point: Greater than 698F.

Upper Explosive Limit: Not Determined

Lower Explosive Limit: Not Determined

**Auto Ignition Temperature:** Estimated to be greater than 734F.

**Extinguishing Media:** Dry Chemical, Water Fog, Foam, Carbon Dioxide. Special Fire Fighting

Procedures: Dense smoke emitted when burned without sufficient oxygen. Possible dust explosion if fines accumulate. Wear standard fire fighting attire

### **Section 6: Spills and Disposal Notification Procedures**

Land Spill: Material should be swept up and discarded.

Water Spill: Clean up and discard or reuse.

Waste Disposal: Dispose of in accordance with local regulations. No special procedures

required.

### Section 7: Handling and Storage Handling

Arline WPC is heavier than normal wood. Lift carefully. Storage: Support every two feet on a flat surface. Store away from strong oxidizing agents or combustible materials.

#### **Section 8: Protective Measures**

**Ventilation:** Use in well ventilated area.

**Respiratory Protection:** An approved respirator may be needed in areas with a high accumulation

of fines.

**Eye protection:** Wear safety glasses with side shields when sawing or installing.

**Skin protection:** No special precautions needed.

## **Section 9: Physical Data Appearance and Odor**

Slight hardwood odor.

Boiling Point: NA

Solubility in Water: Insoluble

Vapor Pressure: Negligible

Freezing Point: NA

Vapor Density: NA

Percent Volatile: Negligible

Specific Gravity: 1.00-1.15 g/cm<sup>3</sup>

## **Section 10: Reactivity Stability**

This material is stable.

Conditions to Avoid: Heat and flame

Materials to Avoid: Strong oxidizing agents

**Combustion Products:** Hazardous Polymerization: Will not occur.

The following combustion

products may be

generated:

carbon dioxide, carbon monoxide, water vapor, trace VOC's, Formic Acid,

Acetic Acid.

### **Section 11: Toxicological Data**

Exposure Limit of Material Not established LD50 of Material Not established Carcinogenetic of Material None (wood dusts are fully stabilized in the polymer Matrix)

### **Section 12: Ecological Considerations**

This material has not been tested for environmental effects.

### **Section 13: Disposal Considerations**

Dispose of as normal refuse.

### **Section 14: Transport Information**

This material is not regulated by DOT.

### **Section 15: Regulatory Information**

Contact Person: ARLINE Composites-Arslan Dis Tic Ltd.Sti

www.arline.com.tr info@arline.com.tr

#### Address:

Sanayi Cad. No:27 35100 Bornova - Izmir / Turkey

Tel: 00 90-232-3889494 Fax: 00 90-232-3880151

